

Endurance

High Density & Focus on Throughput

WITH HP INKJET TECHNOLOGY









NON-CMR, PFAS-FREE

Endurance is an aqueous black ink for HP45a technology producing a high density impression and suitable for high throughput / bulk applications



ENDURANCE | TWK3530

Technical Specifications				
Ink Type	Aqueous			
Color	Black			
Colorant	Hybrid			
Firing Parameters	Voltage: 10.2V Pulse Width: 2.2 ųs			
Pulse Warning	On			
Open Time	~ 1 hr			
Shelf Life	2 yr from MFG			
Bulk Use	Recommended			
Storage Conditions	10°C ~ 30°C			
Operating Conditions	10°C ~ 40°C			
Maintenance	Gently wipe printhead with a dry, lintfree cloth			
Downtime	< 1 day down; leave cartridges in machine, wipe/purge before next use > 1 day down: remove cartridge from machine and seal with cartridge clip, wipe/purge next use			

Note: Performance results depend on individual application parameters, such as substrate, environment, and print orientation.

Performance Data				
Optical Density				
Dry Time				
Decap Time				

For Porous Media

Mill Coat (Matte, Gloss, Dull)

Uncoated Paper / Envelopes Cla

Clay Coated

Application Example			
O.D 100% Coverage Bar	1.14		
Dry Time Size 12 Arial Text	<1s		

600x300DPI, 60# Offset Paper



MFG: 0X/0X/00XX Lot: 012345



Regulatory Compliance					
EuPIA	REACH	Non-	PFAS		
	SVHC	CMR	Free		

